

MAK LOTEX GREASE C

Description

MAK LOTEX GREASE C is calcium based water resistant grease. It does not contain extreme pressure additives

Application

- This is recommended for plain bearings operating in wet conditions where EP property is not required

Benefits

- Good water resistance

Performance Level

- Proprietary grade

Technical Specifications

Characteristics	Test Method	MAK LOTEX C GREASE
Consistency of the Worked Grease at 25°C	ASTM D 217	325
Drop Point, °C	ASTM D 217	98
Free Alkanyity (as Ca(OH) ₂) % by mass,	IS 1448 P:53	0.15
Copper Strip Corrosion Test @ 75°C for 24 hrs.	ASTM D 4048	Negative

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept vertically and should be kept away from dusty or heated areas.
- Lid should not be left open and during handling any contact with dust must be avoided
- Containers used for grease transport should be clean and exclusive

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.

BPCL 'A' Installation, Sewree Fort Road, Sewree (East)

Mumbai -400015

E-mail: MAKcustomercare2@bharatpetroleum.in

Tel No.: 022-24176351