

MAK UNIVEX CD GREASE

Description

MAK UNIVEX CD GREASE Is calcium (lime) based grease specially designed for chassis lubrication of automotive vehicles

Application

This grease is recommended for chassis lubrication of all types of automotive vehicles including commercial vehicles, tractors and other heavy-duty equipment

Benefits

- Good Water Resistance- Gives enhanced life to the grease lubricant and minimum changing intervals
- Smooth & Good Adhesive Properties- adhesiveness makes grease stick long over components and protects them for a long period

Performance Level

- IS 506 :1993 Grade 1

Technical Specifications

Characteristics	Test Method	MAK UNIVEX CD GREASE
Consistency of the Worked Grease at 25°C	ASTM D 217	320
Drop Point, °C	ASTM D 566	100
Free Organic Acidity (as oleic acid), % by mass	IS 1448 P:53	0.2
Free Alkalinity (as Ca(OH) ₂), % by mass	IS 1448 P:53	0.1
Copper Strip Corrosion Test @ 75°C for 24 hrs	ASTM D 4048	Negative

All the mentioned values are typical which may vary from batch to batch

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept vertically and should be kept away from dusty or heated areas
- Lid should not be left open and during handling any contact with dust must be avoided
- Containers used for grease transport should be clean and exclusive

Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred

Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.

BPCL 'A' Installation, Sewree Fort Road, Sewree (East)

Mumbai -400015

E-mail: MAKcustomercare2@bharatpetroleum.in

Tel No.: 022-24176351