

# **MAK FRONT FORK OIL**

## **Description**

MAK Front Fork Oil is blended from high performance group II base oils and fortified with additives to provide superior damping effect thereby increasing life of the forks. It has excellent load carrying ability to ensure smoother ride.

## **Application**

MAK Front Fork Oil is a general market product and specially developed for use in hydraulic front forks of all types of modern motorcycles.

## **Benefits**

- Increases the life of forks
- Provides superior damping effect
- Excellent load carrying capacity
- Suitable for low ambient temperatures

## **Performance Level**

- Proprietary Grade

## **Storage and Handling**

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

## Technical Specifications

Characteristics	ASTM	MAK FRONT FORK OIL
Appearance	--	Clear & Bright
Density @15°C	D1298	0.860
K.V at 40° C, cSt	D445	70.0
Viscosity Index	D2270	118
Flash Point, (COC), °C	D92	220
Pour Point, °C	D97	-27
Copper Strip Corrosion @ 100 Deg. C for 3 hrs.	D130	1a

\*All the mentioned values are typical which may vary from batch to batch.

## Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

## Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.  
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)  
Mumbai -400015  
E-mail: [MAKcustomercare2@bharatpetroleum.in](mailto:MAKcustomercare2@bharatpetroleum.in)  
Tel No.: 022-24176351