

# **MAK PUMP HARIT 40**

## **Description**

Diesel engine oil blended with good quality base oils and additives.

## **Application**

Recommended for diesel engines in agricultural pump sets, threshers, sugarcane crushers etc.

## **Benefits**

- Protection against wear of moving engine parts at all operating conditions
- Protects against rust & corrosion
- Increases engine life
- Ensure trouble free operation

## **PERFORMANCE LEVEL**

- Meets API CC
- SAE 40

## Technical Specifications

Characteristics	ASTM	MAK PUMP HARIT 40
Appearance	--	Clear & Bright
Colour, Visual Observation	--	Brown
Density @ 29.5°C, gm/ml	D1298	0.862
K.V at 100° C, cSt	D445	13.9
Copper Corrosion @ 100° C for 3 hrs	D130	1a
Flash Point, (COC), °C	D92	238
Viscosity Index	D2270	100
Pour Point, °C	D97	-18
Foaming Tendency / Stability: Qty. of foam in ml a) Sequence I b) Sequence II c) Sequence III	D892	Nil / Nil 10 / Nil Nil / Nil

All the mentioned values are typical which may vary from batch to batch.

## Storage and Handling

- Indoor Storage is always preferable.
- Barrels should be kept horizontally with bung position at 3 O'clock 9 O'clock position.
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided.

## Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

## Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

### Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.  
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)  
Mumbai -400015  
E-mail: [MAKcustomercare2@bharatpetroleum.in](mailto:MAKcustomercare2@bharatpetroleum.in)  
Tel No.: 022-24176351