

MAK MOLDOL

Description

MAK MOLDOL is mould release oil blended with fatty acids designed to use in concrete moulding application. These are based on environmentally safe raw materials.

Application

The main application of the mould oil is in concrete fabrication and clay product moulding.

Benefits

- Provide a stain free concrete finish of the highest quality.
- High load bearing capacity
- Present an ecological alternative to the mineral oil based mould release agents.

PERFORMANCE LEVEL

- Proprietary Grade

Technical Specifications

Sr.No	Characteristics	Test method	MAK MOLDOL
1	Appearance	Visual	Light brown
2	Density @ 15°C, Kg/m ³	ASTM D 1298	0.904
3	Flash point COC, °C	ASTM D 92	320
4	Viscosity at 40°C, cSt	ASTM D 445	44.0

All the mentioned values are typical which may vary from batch to batch.

Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bung position at 3'o clock 9 'o clock position
- Barrels should be kept away from dusty or heated areas as much as possible

Health and Safety

These oils are not hazardous under normal conditions of use. For further guidance appropriate Material Safety Data Sheet may be referred.

Advice

For any further advice on applications or otherwise please contact the nearest Bharat Petroleum Territory Office or Technical Services Department at the address given below.

Bharat Petroleum Corporation Ltd.

Product and Application Development Dept.
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)
Mumbai -400015
E-mail: MAKcustomercare2@bharatpetroleum.in
Tel No.: 022-24176351