

# MAK FREEZOLCS

## Description

These are highly refined specially treated straight mineral, paraffinic oils designed for moderate applications

## Application

MAK Freezol CS is recommended for use in any application where temperatures go upto -10 ° C

## Benefits

- Good oxidation stability
- High viscosity index

## Performance Level

- Proprietary grade

## Technical Specifications

| Characteristics                                 | ASTM  | MAK FREEZOL CS       |
|---|-------|----------------------|
|   |       | 68                   |
| Appearance                                      | --    | Bright & Clear fluid |
| Density at 15°C                                 | D1298 | 0.875                |
| K.V at 40° C, cSt                               | D445  | 68.5                 |
| Viscosity Index                                 | D2270 | 105                  |
| Pour Point, °C                                  | D97   | -24                  |
| Flash Point, (COC), °C                          | D92   | 230                  |
| Copper Strip Corrosion Test at 100°C for 3 hrs. | D130  | 1a                   |
| Acidity   |       |                      |
| a) total, mg KOH / g                            |       | 0.03                 |
| b) Inorganic                                    |       | Nil                  |

All the mentioned values are typical which may vary from batch to batch.

## Storage and Handling

- Indoor Storage is always preferable
- Barrels should be kept horizontally with bunk position at 3 O'clock 9 O'clock position
- Barrels should be kept away from dusty or heated areas.
- During handling any contact with dust must be avoided

## Health & Safety

This grade is not hazardous under normal conditions of use. For further guidance Material Safety Data Sheet (MSDS) may be referred.

## Advice

For any further advice on applications or otherwise, please contact the nearest Bharat Petroleum territory office or Technical Services department at the address given below.

### **Bharat Petroleum Corporation Ltd.**

Product and Application Development Dept.  
BPCL 'A' Installation, Sewree Fort Road, Sewree (East)  
Mumbai -400015  
E-mail: [MAKcustomercare2@bharatpetroleum.in](mailto:MAKcustomercare2@bharatpetroleum.in)  
Tel No.: 022-24176351